


Adhesive-Lined Heavy Wall Heatshrink

Features

- 3:1 shrink ratio, not flame-retardant
- Withstands severe mechanical requirements of U.R.D submersible and direct burial installations
- High impact, abrasion, corrosion and chemical resistance
- Rated for 1kv, 90°C application
- Thermoplastic adhesive liner provides complete environmental protection and installation
- Supplied only in 4 ft (1200mm) lengths.

Specifications

Colour:	Black
Material:	Cross linked Polyolefin with Adhesive Lining
Voltage Rating:	600V
Continuous Operating Temperature	-45°C - 110°C
Shrink Temperature	125°C - 200°C
Standards & Compliance:	



Dimensions and Details

Part No:	Size (mm)	As Supplied	Post-Shrunk		Length
		Internal Ø	Internal Ø	Wall Thickness	
HWHS9LTH-1	9	9.00	3.00	2.30	1200
HWHS13LTH-1	13	16.00	4.00	2.75	1200
HWHS20LTH-1	20	19.10	6.00	2.90	1200
HWHS33LTH-1	33	33.00	10.20	3.60	1200
HWHS43LTH-1	43.2	43.20	12.00	5.00	1200
HWHS51LTH-1	51	51.00	16.00	5.00	1200
HWHS70LTH-1	70	70.00	21.00	5.00	1200
HWHS85LTH-1	85	85.00	25.00	5.00	1200
HWHS105LTH-1	105	105.00	30.00	5.10	1200
HWHS120LTH-1	120	120.00	39.00	5.10	1200

Subject to change without notice