

Instrumentation Cable Multipair Overall Screened – LSZH - HV Range

Product Description

Multi Pair, Plain Annealed Copper Conductors, PE Insulated, Overall Screened with an Aluminium/Polyester Laminated Tape with a Tinned Annealed Copper Drain Wire, LSZH Sheathed, UV resistant, Instrumentation Cable

Specifications

Conductor	
Material:	Plain Annealed Copper
Stranding:	Class 2
Standards:	AS/NZS 1125
Insulation	
Material:	PE
Operating Temperature:	70°C
Colour:	Black with white numbered cores White with black numbered cores
Standards:	AS/NZS 3808
Sheath	
Material:	HFS-90-TP (LSZH)
Operating Temperature:	90°C
AS/NZS Material Designation:	5V-90
Colour(s):	Black (UV resistant), Green, Yellow, Blue
Standards:	AS/NZS 3808
Voltage:	0.6/1kV as per standard S008 (not to be connected to mains power)

*MOQ may apply

Product Images



Product Details

Part No.	Colour	No. Of Pairs	Nom. Area mm ²	Cable O.D. mm	Stranding No./mm	Approx Mass kg/km
ELT7301P-SHV	Black	1	0.5	5.3	7/0.30	28
ELT7301P-SHV-GN	Green	1	0.5	5.3	7/0.30	28
ELT7301PBLU-HV	Blue	1	0.5	5.3	7/0.30	28
ELT7302P-SHV	Black	2	0.5	7.5	7/0.30	51
ELT7302PBLU-HV	Blue	2	0.5	7.5	7/0.30	51
ELT7303-SHV	Black	3 Core	0.5	5.8	7/0.30	35
ELT7303-SHV-YLW	Yellow	3 Core	0.5	5.8	7/0.30	35
ELT7303P-SHV	Black	3	0.5	8.3	7/0.30	69
ELT7501PBLU-HV	Blue	1	1.5	7.0	7/0.50	53



Subject to change without notice